

DS-D4518CB162-2FQ/A

DS-D4518CB162-2FQ/A 162" LED AIO LED Module Spare Part



300 × 168.75 Indoor LED Module

- LED modular spare part of DS-D4518CB162-2FQ

▪ Specification

Product Model	
Product Model	DS-D4518CB162-2FQ/A
Product Type	
Product Type	Small Pixel Pitch Indoor Full-color LED Display
Cabinet	
Pixel Configuration	SMD Triad LED (with glue)
Pixel Pitch Category	P1.8
Pixel Pitch	1.875 mm
Pixel Density	284444 dots/m ²
Module	
Dimensions	300 × 168.75 mm
Module Resolution	160 × 90
Display	
White Balance Brightness	600 cd/m ²
Color Temperature	3000-10000 K adjustable
Viewing Angle	160°(H)/160°(V)
Contrast Ratio	3000:1
Color Uniformity	≤ ± 0.003Cx , Cy
Brightness Uniformity	≥ 97%
Processing Performance	
Driving Method	Constant current driving
Frame Frequency	60 Hz
Refresh Rate	3840 Hz
Grey Level	16 bit
Power	
Input Voltage	100~240 VAC ± 10%
Working Environment	
Working Temperature	-10 °C to 40 °C (14 °F to 104 °F)
Working Humidity	20% to 80% RH (without condensation)
Storage Temperature	-10 °C to 50 °C (14 °F to 122 °F)
Storage Humidity	10% to 90% RH (without condensation)
General	
G.W.	0.4 kg
Net Weight	0.366 kg

▪ Available Model

DS-D4518CB162-2FQ/A(All-in-one)

See Far, Go Further



www.hikvision.com
support@hikvision.com

